



S-LIB-M003 Sensor

Solar Radiation (Silicon Pyranometer) Smart Sensor

Effectively measure light levels with this silicon pyranometer sensor. The Solar Radiation Smart Sensor enables rapid deployment. Since HOBO data loggers recognize this sensor, no complicated programming or setup is required. This product offers a measurement range of 0 to 1280 W/m² over a spectral range of 300 to 1100 nm. A measurement averaging mode is available.

Also available in a wireless model for use with the HOBOnet Field Monitoring System.

Supported Measurements:

Light Intensity and Solar Radiation

Key Advantages:

- Measurement range of 0 to 1280 W/m² over a spectral range of 300 to 1100 nm
- Plug-n-play smart sensor
- Compatible with H21, H22, and U30 family loggers



S-LIB-M003 Sensor Specifications

Measurement range: 0 to 1280 W/m²

Operating temperature range: -40° to 75°C (-40° to 167°F)

Accuracy: ±10 W/m² or ±5%, whichever is greater in sunlight. Additional temperature induced error ±0.38 W/m² /°C from 25°C (0.21 W/m² /°F from 77°F)

Resolution: 1.25 W/m²

Drift: <±2% per year

Spectral range: 300 to 1100 nm

Cosine response error: ±5%, 0° to 70°; ±10%, 70° to 80° from vertical

Azimuth error: ±2% error at 45° from vertical, 360° rotation

Calibration: Factory recalibration available

Housing: anodized aluminum housing with acrylic diffuser and o-ring seal

Dimensions: 4.1 cm high x 3.2 cm diameter (1 5/8 in. x 1 1/4 in.)

Approximate weight: 120 g (4 oz)

Cable length: 3 m (9.8 ft)

Length of Smart Sensor Network Cable: 3 m

Measurement parameters: average over logging interval, user-defined sampling interval from 1 second

Note: Light sensor bracket (M-LBA) and light sensor level (M-LLA) recommended

CE - The CE Marking identifies this product as complying with all relevant directives in the European Union (EU)

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

▶ Email sales@onsetcomp.com

▶ Call 1-508-759-9500

▶ In U.S. toll free 1-800-564-4377

▶ Fax 1-508-759-9100

Technical Support (8am to 8pm ET, Monday through Friday)

▶ Contact Product Support www.onsetcomp.com/support/contact

▶ Call 1-508-759-9500

▶ In U.S. toll free 1-877-564-4377

Onset Computer Corporation

470 MacArthur Boulevard

Bourne, MA 02532



METRICS

Metrics GmbH • Elberfelder Str. 19-21 • 58095 Hagen

Telefon: 02331 3483086 • Telefax: 02331 3483088

E-Mail: info@metrics24.de • <https://www.metrics24.de>