



HOBO® UX90 Loggers

Next-generation time-of-use loggers for fast, reliable monitoring

The award-winning HOBO UX90 Series is the industry's lowest-cost, most comprehensive family of "time-of-use" data loggers. The new toolbox suite includes LCD-display data loggers for measuring motor on/off status, electronic pulses, state changes, and occupancy and light-use patterns.

Leveraging patent-pending technology, HOBO UX90 data loggers streamline energy audits and make field deployment fast and reliable.

Supported Measurements: State, Pulse, Event, Runtime, Light On/Off, Motor On/Off, Occupancy/Light

Key Advantages:

- LCD displays Time On or % On, providing instant feedback
- Auto-calibration & signal strength indicator ensure proper deployment
- 84k measurement capacity enables long deployments
- Rare-earth magnets, 3M Command™ Strips, or mounting tabs for reliable mounting
- Flexible logger Start and Stop options
- HOBOWare Pro allows for easy setup of hundreds of loggers

Minimum System Requirements:



Software



USB cable*



*USB cable included with software part # BHW-PRO-USB

For the most accurate readings, use of Light Pipe UX90-LIGHT-PIPE-1 is recommended to eliminate the effects of ambient light.

► For complete information and accessories, please visit: www.onsetcomp.com

Part number	UX90-001 (State)	UX90-002 (Light On/Off)	UX90-004 (Motor On/Off)	UX90-006 (Occupancy/Light)
Memory	84,000 measurements			
INTERNAL SENSOR				
Maximum state, event, runtime frequency	1 Hz	--	--	--
Light threshold	--	65 lux	--	65 lux
Light type	--	LED, CFL, fuorescent, HID, incandescent, natural	--	LED, CFL, fuorescent, HID, incandescent, natural
AC magnetic field threshold	--	--	> 40 mGauss at 60 Hz	--
Maximum sensor detection range	--	--	--	12 m (39.4 ft)
EXTERNAL INPUT				
External contact input	solid state closure or logic driven voltage output		--	solid state closure
Maximum state, event, runtime frequency	1 Hz	--	1 Hz	--
Maximum Pulse Frequency	50 Hz	--	--	--
Battery life	1 year typical, user replaceable, CR2032			
Operating range	-20° to 70°C (-4° to 158°F); 0-95% RH (non-condensing)			
Dimensions	3.66 x 5.94 x 1.52 cm (1.44 x 2.34 x 0.6 in)		3.66 x 8.48 x 1.52 cm (1.44 x 3.34 x 0.6 in)	3.66 x 8.48 x 2.87 cm (1.44 x 3.34 x 1.13 in)
CE compliant	Yes			

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- Email sales@onsetcomp.com
- Call 1-508-759-9500
- In U.S. toll free 1-800-564-4377
- Fax 1-508-759-9100

Technical Support (8am to 8pm ET, Monday through Friday)

- Contact Product Support onsetcomp.com/support/contact
- Call 1-508-759-9500
- In U.S. toll free 1-877-564-4377

Onset Computer Corporation
470 MacArthur Boulevard
Bourne, MA 02532



METRICS

Metrics GmbH • Elberfelder Str. 19-21 • 58095 Hagen
Telefon: 02331 3483086 • Telefax: 02331 3483088
E-Mail: info@metrics24.de • <https://www.metrics24.de>